#	Type	L #	Hits	Search Text	DBs
1	BRS	L1	14276	matrix near5 (reading or readout or $5detector$2 or $5sensor$2)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
2	BRS	L2	117786	imag$5 near3 ($5detector$2 or $5sensor$2)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
3	BRS	L4	41021	impedance near4 match$5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
4	BRS	L5	3631	variation near2 charge	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
5	BRS	L6	162968	bus and current	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
6	BRS	L8	98141	capacit$5 and transistor and amplifier and voltage	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
7	BRS	L9	1	1 and 2 and 3 and 4 and 5 and 6 and 8 and @ad<=20000410	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
8	IS&R	L10	2	("5742058").PN.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
9	BRS	L11	1	10 and 5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
10	IS&R	L12	2	("6201248").PN.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
11	BRS	L13	1	12 and 5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
12	BRS	L14	2	1 and 3 and 4 and 5 and 6 and 8 and @ad<=20000410	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
13	BRS	L15	2	1 and 3 and 5 and 6 and 8 and @ad<=20000410	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
14	BRS	L17	1	10 and 4	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
15	BRS	L18	1273	1 and 250/$.ccls. and @ad<=20000410	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
16	BRS	L19	15	18 and 5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB